PRODUCT DATA SHEET

STAINLESS STEEL

ROUND Water Tanks



900mm - 3700mm

select WATER TANKS

This Stainless Steel corrugated round rainwater tank can be built to hold small and large volumes of water and it not only looks good, but it is sustainable, hygienic and comes with a 30-year non corrosion with a 15-year manufacturing Warranty.

Features & Benefits:

- > Can be custom made to size
- > Made from 304 or 316 Stainless steel
- > Comes with a 30-year corrosion warranty
- > Capacity can be up to 29,838 litres
- > Choose to contrast or feature with any structures
- > Hygienic as no leeching by the stainless steel
- > Reflects heat and keeps the water cool
- > All steel with no plastic lining and recyclable
- > Minimal emissions footprint in manufacture
- > Comes with Inlet, Overflow and Outlet fittings
- > You can nominate positions of the fittings
- Can be placed on concrete, crusher dust or timber structures
- > Can withstand Australia's harsh conditions
- > Bushfire resistant by keeping its structural integrity
- Family owned company in SE Queensland
- > Come checked for quality assurance

Recommended for:

- > Storage of a large volume of water
- > Modern design to blend with architectural features
- > Storage of drinking water
- > Agricultural and horticultural purposes
- > The harsh Australian climate
- > Withstanding bushfires

Inclusions

- Inlet strainer (400mm) to strain debris, to shield water from light, and reduce algae growth
- Overflow fitting (90 or 100mm) with inbuilt SS gauze to prevent mosquitoes from entering
- Outlet fitting: A 25mm outlet and ball valve (A range of additional fitting can also be ordered)

Select Water Tanks 57-63 Centenary Place, Logan Village Qld 4207 E: sales@selectwatertanks.com.au
Ph: 07 5546 8571
www.selectwatertanks.com.au

Specifications	
Height	300mm to 3100 mm
Diameter	900mm to 3700 mm
Minimum volume	190 litres
Maximum volume	29,838 litres
Wall	Roll formed 0.55 304/316 stainless steel (corrugated)
Base	Flat 0.55 304/316 stainless steel
Lid	Flat 0.55 304/316 stainless steel
Jointing	Electric resistance welding
Sealant	Neutral cure silicone sealant AS 4020/BS 5889 Approved
Thermal resistance	Temperatures to 165 degrees Celsius

Warranty

- 30-year minimum life due to corrosion, and
- 15-year construction warranty covering the assembly of the tank from date of purchase.

